designed and created for your needs



4x320W 48V LED - 8.5M









4x320W 48V LED - 8.5M





APPLICATIONS











FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 48V power between the generator and the lights
- № 7 section hydraulic vertical tower 8.5 m, 340° rotatable
- Galvanised metalworks
- Very compact dimensions, up to 12 units per truck
- Central lifting eye, 4 side forklift pockets for effective handling
- Plug & Play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button

- 4 height adjustable stabilisers
- Amoss safety system

| Dimensions & Weight | |
|-------------------------|------------------------|
| Dimensions min (mm) | 2540x1390x2420 (LxWxH) |
| Dimensions max (mm) | 2540x1550x8500 (LxWxH) |
| Total weight (kg) | 932 |
| Floodlights | |
| Туре | LED |
| Power (each) | 320W |
| Floodlights number | 4 |
| Options | Timer |
| Illuminated area (sqm) | 9300 |
| Mast | |
| Lifting Method | Hydraulic |
| Max Height | 8.5 m |
| Rotation | 340° |
| Max Wind Speed | 110 km/h |
| Alternator | |
| Model | Synchronous |
| Frequency (Hz) | 50 |
| Insulation class | Н |
| Degree of protection | IP 23 |
| Single phase voltage | 3.5 KVA - 230V |
| Auxiliary outlets | 1KVA |
| Engine | |
| Model | Kubota Z482* |
| Fuel | Diesel |
| r.p.m. | 1500 |
| Tank capacity (I) | 110 |
| Consumption (I/h) | 0.55 |
| Running time | 200 h |
| Noise level dB(A) at 7m | 65 |

^{*} May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

