

BATTERY Line

Leader in  
Sustainability



Zero Emissions



Zero Fuel



Zero Noise



1300 sqm Bright, Instant  
LED Light



Operation: **100% BATTERY**  
Rated voltage 24V, 200ah

# X-RAIL KIT

24V, 200AH +9 MAST - LED



9 cables (9m each) included in the KIT

## BATTERY Line

### Features

- 24V, 200Ah lithium battery built-in
- External battery charger 24V 80A 230V 1Ph
- Mains input 230V 16A
- Battery charge gauge
- Floodlights hour meter
- Rechargeable lithium battery
- Full aluminum body
- 2 Tubular frames for manual handling
- 9 external connectable masts
- Maximum mast height 3225mm (each mast)
- Manual lifting system
- 80 µm powder coating
- **Very compact dimensions for easy handling & transportability, (X-Rail + External Battery Charger + 9 External Masts)**
- Light weight for improved manoeuvrability
- 41 hrs running time from battery
- ± 3h40 min. recharge
- 9 cables (9m each) included in the KIT

## ZERO Emissions – ZERO Fuel – ZERO Noise

#### Dimensions and Weight

Dimensions (mm) LxWxH	858 x 333 x 590
Weight (kg)	56

#### Battery

Type	Lithium
Battery number	1
Rated voltage	24V, 200 ah
Running time	41 h
Charging time with floodlights off	± 3h40 min
Expected battery cycle	2000
Expected battery life	60000 hrs

#### External Battery Charger

Dimensions (mm) LxWxH	867x627x3120
Weight (kg)	13
Type	24V 80A
Mains input	230V 16A

#### Floodlights (External Mast)

Type	Led
Quantity	9
Power (each)	13W
IP level	65
Illuminated area (sqm)	1300

#### External Mast

Dimensions min. each (mm)	500 x 1827
Dimensions max. each (mm)	500 x 3220
Lifting method	Manual
Weight each (kg)	12
Max. wind Speed	110 km/h